

CDL120-60-2

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000887

Scan to open this online



FLOW RANGE

60 - 150 m³/h

HEAD RANGE

92.5 - 128 m

MOTOR

55 kW

SPEED


2900 rpm

Specifications

Series	CDL / CDLF
Size	CDL120
Stages	6
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	55 kW (75 hp)
Max pressure	16 bar
Connection	DN125
Weight	641 kg
Variant	2
Data basis	Published performance curve (Performance table, printed pp. 39–40)

Performance curve

Head versus flow - CDL120-60-2, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
60	128
70	125.5
80	123



Flow (m³/h)	Head (m)
90	121
100	117.3
110	113.5
120	110
130	104.5
140	98.5
150	92.5

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	1670
B2	B2 — upper section height: motor	760
B1_B2	B1+B2 — overall height	2430
D1	D1 — motor diameter	540
D2	D2 — base / flange width	370
-	Net weight	641

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-DC7AE. Contact: +92 345 9547419 sales@cnppakistan.com