

CDL150-30-1

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000893

Scan to open this online



FLOW RANGE

80 - 180 m³/h

HEAD RANGE

45 - 70 m

MOTOR

37 kW

SPEED


2900 rpm

Specifications

Series	CDL / CDLF
Size	CDL150
Stages	3
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	37 kW (50 hp)
Max pressure	16 bar
Connection	DN125
Weight	395 kg
Variant	1
Data basis	Published performance curve (Performance table, printed pp. 41–42)

Performance curve

Head versus flow - CDL150-30-1, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
80	70
90	68
100	67



Flow (m³/h)	Head (m)
110	65
120	63
130	62
140	60
150	56
160	53
170	49
180	45

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	1160
B2	B2 — upper section height: motor	650
B1_B2	B1+B2 — overall height	1810
D1	D1 — motor diameter	400
D2	D2 — base / flange width	310
-	Net weight	395

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-80BC3. Contact: +92 345 9547419 sales@cnppakistan.com