

CDL32-100

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000450

Scan to open this online



FLOW RANGE

16 - 40 m³/h

HEAD RANGE

98 - 182 m

MOTOR

18.5 kW


SPEED

2900 rpm

Specifications

Series	CDL / CDLF
Size	CDL32
Stages	10
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	18.5 kW (25 hp)
Max pressure	29 bar
Connection	DN65
Weight	232 kg
Data basis	Published performance curve (Performance table, printed pp. 31–32)

Performance curve



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
16	182
20	173
24	164
28	152



Flow (m³/h)	Head (m)
32	138
36	122
40	98

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	1240
B2	B2 — upper section height: motor	550
B1_B2	B1+B2 — overall height	1790
D1	D1 — motor diameter	330
D2	D2 — base / flange width	255
-	Net weight	232

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261027-0DA17. Contact: +92 345 9547419 sales@cnppakistan.com