

CDL42-30-2

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000507

Scan to open this online



FLOW RANGE

25 - 55 m³/h

HEAD RANGE

38 - 63 m

MOTOR

11 kW

SPEED


2900 rpm

Specifications

Series	CDL / CDLF
Size	CDL42
Stages	3
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	11 kW (15 hp)
Max pressure	30 bar
Connection	DN80
Weight	187 kg
Variant	2
Data basis	Published performance curve (Performance table, printed pp. 33–34)

Performance curve

Head versus flow - CDL42-30-2, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
25	63
30	61
35	58



Flow (m³/h)	Head (m)
40	54
42	52
45	50
50	44
55	38

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	826
B2	B2 — upper section height: motor	500
B1_B2	B1+B2 — overall height	1326
D1	D1 — motor diameter	330
D2	D2 — base / flange width	255
-	Net weight	187

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261027-3BAF0. Contact: +92 345 9547419 sales@cnppakistan.com