

CDL42-60-2

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-001239

Scan to open this online



FLOW RANGE

25 - 55 m³/h

HEAD RANGE

85 - 135 m

MOTOR

22 kW

SPEED


2900 rpm

Specifications

Series	CDL / CDLF
Size	CDL42
Stages	6
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	22 kW (30 hp)
Max pressure	30 bar
Connection	DN80
Weight	266 kg
Variant	2
Data basis	Published performance curve (Performance table, printed pp. 33–34)

Performance curve

Head versus flow - CDL42-60-2, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
25	135
30	130
35	124



Flow (m³/h)	Head (m)
40	117
42	113
45	108
50	97
55	85

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	1066
B2	B2 — upper section height: motor	575
B1_B2	B1+B2 — overall height	1641
D1	D1 — motor diameter	360
D2	D2 — base / flange width	285
-	Net weight	266

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-90734. Contact: +92 345 9547419 sales@cnppakistan.com