

CDL85-60-2

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-001140

Scan to open this online



FLOW RANGE

50 - 110 m³/h

HEAD RANGE

86 - 155 m

MOTOR

45 kW

SPEED


2900 rpm

Specifications

Series	CDL / CDLF
Size	CDL85
Stages	6
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	45 kW (60 hp)
Max pressure	17 bar
Connection	DN100
Weight	428 kg
Variant	2
Data basis	Published performance curve (Performance table, printed pp. 37–38)

Performance curve

Head versus flow - CDL85-60-2, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
50	155
60	148
70	139



Flow (m³/h)	Head (m)
80	129
85	122
90	117
100	102
110	86

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	1141
B2	B2 — upper section height: motor	685
B1_B2	B1+B2 — overall height	1826
D1	D1 — motor diameter	460
D2	D2 — base / flange width	340
-	Net weight	428

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-04A64. Contact: +92 345 9547419 sales@cnppakistan.com