

CDL3-12

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000825

Scan to open this online



FLOW RANGE

1.5 - 5 m³/h

HEAD RANGE

52 - 104 m

MOTOR

2.2 kW

SPEED


3500 rpm

Specifications

Series	CDL / CDLF
Size	CDL3
Stages	12
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	2.2 kW (3 hp)
Max pressure	22 bar
Connection	DN25
Weight	37 kg
Data basis	Published performance curve (Performance table, printed pp. 17–18)

Performance curve

Head versus flow - CDL3-12, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
1.5	104
2	100
2.5	96
3	90



Flow (m³/h)	Head (m)
3.5	79
4	73
4.5	63
5	52

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	458
B2	B2 — upper section height: motor	290
B1_B2	B1+B2 — overall height	748
D1	D1 — motor diameter	190
D2	D2 — base / flange width	155
-	Net weight	37

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-2AEEC. Contact: +92 345 9547419 sales@cnppakistan.com