

CDL65-30

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-001382

Scan to open this online



FLOW RANGE

40 - 100 m³/h

HEAD RANGE

65 - 112 m

MOTOR

30 kW

SPEED


3500 rpm

Specifications

Series	CDL / CDLF
Size	CDL65
Stages	3
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	30 kW (40 hp)
Max pressure	22 bar
Connection	DN100
Weight	313 kg
Data basis	Published performance curve (Performance table, printed pp. 35–36)

Performance curve

Head versus flow - CDL65-30, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
40	112
50	108
60	100
65	96



Flow (m³/h)	Head (m)
70	93
80	86
90	77
100	65

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	836
B2	B2 — upper section height: motor	650
B1_B2	B1+B2 — overall height	1486
D1	D1 — motor diameter	400
D2	D2 — base / flange width	310
-	Net weight	313

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-CD469. Contact: +92 345 9547419 sales@cnppakistan.com