

CDL8-6

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000824

Scan to open this online



FLOW RANGE

7 - 14 m³/h

HEAD RANGE

57 - 85 m

MOTOR

4 kW

SPEED


3500 rpm

Specifications

Series	CDL / CDLF
Size	CDL8
Stages	6
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	4 kW (5.5 hp)
Max pressure	21 bar
Connection	DN40
Weight	58 kg
Data basis	Published performance curve (Performance table, printed pp. 21–22)

Performance curve

Head versus flow - CDL8-6, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
7	85
8	82
9	78
10	76



Flow (m³/h)	Head (m)
11	72
12	68
13	62
14	57

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	487
B2	B2 — upper section height: motor	355
B1_B2	B1+B2 — overall height	842
D1	D1 — motor diameter	230
D2	D2 — base / flange width	188
-	Net weight	58

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-57E89. Contact: +92 345 9547419 sales@cnppakistan.com