

CDL85-20-2

CDL / CDLF | Vertical multistage centrifugal pump



CNP-M-000544

Scan to open this online



FLOW RANGE

60 - 130 m³/h

HEAD RANGE

22 - 59 m

MOTOR

18.5 kW

SPEED


3500 rpm

Specifications

Series	CDL / CDLF
Size	CDL85
Stages	2
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	18.5 kW (25 hp)
Max pressure	17 bar
Connection	DN100
Weight	211 kg
Variant	2
Data basis	Published performance curve (Performance table, printed pp. 37–38)

Performance curve

Head versus flow - CDL85-20-2, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
60	59
70	57
80	54



Flow (m³/h)	Head (m)
85	51
90	48
100	44
110	39
120	32
130	22

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	773
B2	B2 — upper section height: motor	550
B1_B2	B1+B2 — overall height	1323
D1	D1 — motor diameter	330
D2	D2 — base / flange width	255
-	Net weight	211

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261027-8CB11. Contact: +92 345 9547419 sales@cnppakistan.com