

CDLF3-19+CDH3-25

CDLF + CDH | High-pressure pump



CNP-M-000570

Scan to open this online



FLOW RANGE

1.5 - 5 m³/h

HEAD RANGE

190 - 378 m

MOTOR

7 kW

SPEED


3500 rpm

Specifications

Series	CDLF + CDH
Size	CDLF3+CDH3
Stages	19
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	7 kW
Max pressure	44 bar
Connection	PJE coupling
Weight	106 kg
Data basis	Published performance curve (Performance table, printed pp. 35–36)

Performance curve

Head versus flow - CDLF3-19+CDH3-25, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m³/h)	Head (m)
1.5	378
2	368
2.5	352
3	328



Flow (m³/h)	Head (m)
3.5	297
4	271
4.5	234
5	190

Dimensions (mm)

Code	Description	Value
B1	B1 — lower section height: base to motor flange	594
B2	B2 — upper section height: motor	345
B1_B2	B1+B2 — overall height	939
D1	D1 — motor diameter	197
D2	D2 — base / flange width	165
-	Net weight	106

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261027-B91B8. Contact: +92 345 9547419 sales@cnppakistan.com