

CDLK20-60/6

CDLK / CDLKF (immersion) | Vertical multistage centrifugal pump



CNP-M-001631

Scan to open this online



FLOW RANGE

12 - 34 m³/h

HEAD RANGE

70 - 118 m

MOTOR

11 kW

SPEED


3500 rpm

Specifications

Series	CDLK / CDLKF (immersion)
Size	CDLK20
Stages	6
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	11 kW (15 hp)
Max pressure	23 bar
Connection	Thread G2"
Weight	132 kg
Data basis	Published performance curve (Performance table, printed pp. 43–44)

Performance curve

Head versus flow - CDLK20-60/6, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
12	118
16	113
20	108
24	102



Flow (m³/h)	Head (m)
28	91
32	77
34	70

Dimensions (mm)

Code	Description	Value
A	A — overall height	1051
B	B — immersion length	351
C	C — motor height	700
D	D	255
D1	D1 — motor diameter	330
-	Net weight	132

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-A24E8. Contact: +92 345 9547419 sales@cnppakistan.com