

CDLK3-210/21

CDLK / CDLKF (immersion) | Vertical multistage centrifugal pump



CNP-M-001724

Scan to open this online



FLOW RANGE

1.5 - 5 m³/h

HEAD RANGE

91 - 183 m

MOTOR

3 kW

SPEED


3500 rpm

Specifications

Series	CDLK / CDLKF (immersion)
Size	CDLK3
Stages	21
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	3 kW (4 hp)
Max pressure	22 bar
Connection	Thread G1 1/4"
Weight	38 kg
Data basis	Published performance curve (Performance table, printed pp. 35–36)

Performance curve

Head versus flow - CDLK3-210/21, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
1.5	183
2	178
2.5	170
3	160



Flow (m³/h)	Head (m)
3.5	141
4	129
4.5	112
5	91

Dimensions (mm)

Code	Description	Value
A	A — overall height	943
B	B — immersion length	465
C	C — motor height	478
D	D	165
D1	D1 — motor diameter	197
-	Net weight	38

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-CC9B0. Contact: +92 345 9547419 sales@cnppakistan.com