

CDLK3-90/9

CDLK / CDLKF (immersion) | Vertical multistage centrifugal pump



CNP-M-001674

Scan to open this online



FLOW RANGE

1.5 - 5 m³/h

HEAD RANGE

40 - 78 m

MOTOR

1.5 kW

SPEED


3500 rpm

Specifications

Series	CDLK / CDLKF (immersion)
Size	CDLK3
Stages	9
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	1.5 kW (2 hp)
Max pressure	22 bar
Connection	Thread G1 1/4"
Weight	27 kg
Data basis	Published performance curve (Performance table, printed pp. 35–36)

Performance curve

Head versus flow - CDLK3-90/9, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m³/h)	Head (m)
1.5	78
2	77
2.5	72
3	68



Flow (m³/h)	Head (m)
3.5	60
4	56
4.5	50
5	40

Dimensions (mm)

Code	Description	Value
A	A — overall height	662
B	B — immersion length	249
C	C — motor height	413
D	D	155
D1	D1 — motor diameter	190
-	Net weight	27

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-2E7BE. Contact: +92 345 9547419 sales@cnppakistan.com