

CDLK32-40/4-2

CDLK / CDLKF (immersion) | Vertical multistage centrifugal pump



CNP-M-001088

Scan to open this online



FLOW RANGE

20 - 48 m³/h

HEAD RANGE

45 - 94 m

MOTOR

11 kW

SPEED


3500 rpm

Specifications

Series	CDLK / CDLKF (immersion)
Size	CDLK32
Stages	4
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	11 kW (15 hp)
Max pressure	26 bar
Connection	DIN flange DN65
Weight	155 kg
Variant	2
Data basis	Published performance curve (Performance table, printed pp. 45–46)

Performance curve

Head versus flow - CDLK32-40/4-2, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
20	94
24	91
28	87



Flow (m³/h)	Head (m)
32	81
36	73
40	65
44	56
48	45

Dimensions (mm)

Code	Description	Value
A	A — overall height	1121
B	B — immersion length	403
C	C — motor height	718
D	D	255
D1	D1 — motor diameter	330
-	Net weight	155

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-D7AC1. Contact: +92 345 9547419 sales@cnppakistan.com