

CDLK8-30/3

CDLK / CDLKF (immersion) | Vertical multistage centrifugal pump



CNP-M-000756

Scan to open this online



FLOW RANGE

7 - 14 m³/h

HEAD RANGE

28 - 41 m

MOTOR

2.2 kW

SPEED


3500 rpm

Specifications

Series	CDLK / CDLKF (immersion)
Size	CDLK8
Stages	3
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	2.2 kW (3 hp)
Max pressure	21 bar
Connection	Thread G2"
Weight	37 kg
Data basis	Published performance curve (Performance table, printed pp. 39–40)

Performance curve

Head versus flow - CDLK8-30/3, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
7	41
8	40
9	38
10	37



Flow (m³/h)	Head (m)
11	35
12	33
13	30
14	28

Dimensions (mm)

Code	Description	Value
A	A — overall height	590
B	B — immersion length	171
C	C — motor height	419
D	D	155
D1	D1 — motor diameter	190
-	Net weight	37

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-67CA3. Contact: +92 345 9547419 sales@cnppakistan.com