CNP PUMPS PAKISTAN

CDM3-15

CDM / CDMF | Vertical multistage centrifugal pump

CNP-M-001363

Scan to open this online

FLOW RANGE	HEAD RANGE	MOTOR	SPEED
1.2 - 4.4 m³/h	**51 - 113 m**	**1.5 kW**	**2900 rpm**

Specifications

Series	**CDM / CDMF**
Size	**CDM3**
Stages	**15**
Mains frequency	**50 Hz**
Speed	**2900 rpm**
Motor power	**1.5 kW (2 hp)**
Max pressure	**23 bar**
Connection	**DIN flange DN25**
Weight	**40 kg**
Data basis	**Published performance curve (Performance table printed p. 13; dimensions p. 37)**

Performance curve



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m³/h)	Head (m)
0	113
1.2	110
1.6	108
2	105

Flow (m^3/h)	Head (m)
2.4	100
2.8	94
3	90
3.2	86
3.6	76
4	64
4.4	51

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	467
H2	H2 — motor height	293
H	H — overall height, flange	835
H_oth	H — overall height, other connections	810
D1	D1 — motor diameter	172
D2	D2 — base / flange width	120
weight_cdmf_kg	Net weight CDMF	36
-	Net weight	40

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-7A9F3. Contact: +92 345 9547419 sales@cnppakistan.com