

CDM32-10

CDM / CDMF | Vertical multistage centrifugal pump



CNP-M-000106

Scan to open this online



FLOW RANGE

16 - 40 m³/h

HEAD RANGE

98 - 193 m

MOTOR

18.5 kW

SPEED


2900 rpm

Specifications

Series	CDM / CDMF
Size	CDM32
Stages	10
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	18.5 kW (25 hp)
Max pressure	29 bar
Connection	DIN flange DN65
Weight	221 kg
Data basis	Published performance curve (Performance table printed p. 23; dimensions p. 42)

Performance curve

Head versus flow - CDM32-10, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0	193
16	182
20	173
24	164



Flow (m³/h)	Head (m)
28	152
32	138
36	122
40	98

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	1080
H2	H2 — motor height	545
H	H — overall height, flange	1730
D1	D1 — motor diameter	330
D2	D2 — base / flange width	205
weight_cdmf_kg	Net weight CDMF	217
-	Net weight	221

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-BA67D. Contact: +92 345 9547419 sales@cnppakistan.com