

CDM32-5-2

CDM / CDMF | Vertical multistage centrifugal pump



CNP-M-000977

Scan to open this online



FLOW RANGE

16 - 40 m³/h

HEAD RANGE

41 - 92 m

MOTOR

11 kW

SPEED


2900 rpm

Specifications

Series	CDM / CDMF
Size	CDM32
Stages	5
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	11 kW (15 hp)
Max pressure	29 bar
Connection	DIN flange DN65
Weight	184 kg
Variant	2
Data basis	Published performance curve (Performance table printed p. 23; dimensions p. 42)

Performance curve

Head versus flow - CDM32-5-2, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0	92
16	83
20	79



Flow (m³/h)	Head (m)
24	74
28	68
32	60
36	52
40	41

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	730
H2	H2 — motor height	500
H	H — overall height, flange	1335
D1	D1 — motor diameter	330
D2	D2 — base / flange width	205
weight_cdmf_kg	Net weight CDMF	179
-	Net weight	184

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-BC5C8. Contact: +92 345 9547419 sales@cnppakistan.com