CNP PUMPS PAKISTAN

CDM5-9

CDM / CDMF | Vertical multistage centrifugal pump

CNP-M-000928

Scan to open this online

FLOW RANGE	HEAD RANGE	MOTOR	SPEED
2.5 - 8.5 m³/h	**27 - 67 m**	**1.5 kW**	**2900 rpm**

Specifications

Series	**CDM / CDMF**
Size	**CDM5**
Stages	**9**
Mains frequency	**50 Hz**
Speed	**2900 rpm**
Motor power	**1.5 kW (2 hp)**
Max pressure	**24 bar**
Connection	**DIN flange DN32**
Weight	**38 kg**
Data basis	**Published performance curve (Performance table printed p. 15; dimensions p. 38)**

Performance curve

Head versus flow - CDM5-9, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m³/h)	Head (m)
0	67
2.5	64
3	63
4	60

Flow (m^3/h)	Head (m)
5	55
6	49.5
7	41.5
8	31.5
8.5	27

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	410
H2	H2 — motor height	293
H	H — overall height, flange	778
H_oth	H — overall height, other connections	753
D1	D1 — motor diameter	172
D2	D2 — base / flange width	120
weight_cdmf_kg	Net weight CDMF	33
-	Net weight	38

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-B9D86. Contact: +92 345 9547419 sales@cnppakistan.com