

CDM85-5-2

CDM / CDMF | Vertical multistage centrifugal pump



CNP-M-000112

Scan to open this online



FLOW RANGE

50 - 110 m³/h

HEAD RANGE

68 - 150 m

MOTOR

37 kW

SPEED


2900 rpm

Specifications

Series	CDM / CDMF
Size	CDM85
Stages	5
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	37 kW (50 hp)
Max pressure	17 bar
Connection	DIN flange DN100
Weight	359 kg
Variant	2
Data basis	Published performance curve (Performance table printed p. 29; dimensions p. 45)

Performance curve

Head versus flow - CDM85-5-2, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0	150
50	126
60	120



Flow (m³/h)	Head (m)
70	113
80	104
85	98
90	93
100	81
110	68

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	851
H2	H2 — motor height	650
H	H — overall height, flange	1641
D1	D1 — motor diameter	418
D2	D2 — base / flange width	256
weight_cdmf_kg	Net weight CDMF	350
-	Net weight	359

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261027-2CF49. Contact: +92 345 9547419 sales@cnppakistan.com