

CDM10-12

CDM / CDMF | Vertical multistage centrifugal pump



CNP-M-000659

Scan to open this online



FLOW RANGE

6 - 17 m³/h

HEAD RANGE

98 - 197 m

MOTOR

7.5 kW

SPEED


3500 rpm

Specifications

Series	CDM / CDMF
Size	CDM10
Stages	12
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	7.5 kW (10 hp)
Max pressure	24 bar
Connection	DIN flange DN40
Weight	92 kg
Data basis	Published performance curve (Performance table printed p. 17; dimensions p. 39)

Performance curve

Head versus flow - CDM10-12, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0	197
6	187
8	180
10	169



Flow (m ³ /h)	Head (m)
12	154
14	136
16	112
17	98

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	665
H2	H2 — motor height	390
H	H — overall height, flange	1135
D1	D1 — motor diameter	260
D2	D2 — base / flange width	168
weight_cdmf_kg	Net weight CDMF	90
-	Net weight	92

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-6AF2E. Contact: +92 345 9547419 sales@cnppakistan.com