

CDM10-4

CDM / CDMF | Vertical multistage centrifugal pump



CNP-M-000227

Scan to open this online



FLOW RANGE

6 - 17 m³/h

HEAD RANGE

30.5 - 64 m

MOTOR

3 kW

SPEED


3500 rpm

Specifications

Series	CDM / CDMF
Size	CDM10
Stages	4
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	3 kW (4 hp)
Max pressure	24 bar
Connection	DIN flange DN40
Weight	53 kg
Data basis	Published performance curve (Performance table printed p. 17; dimensions p. 39)

Performance curve

Head versus flow - CDM10-4, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0	64
6	60.5
8	58
10	54



Flow (m³/h)	Head (m)
12	49
14	43.5
16	35.5
17	30.5

Dimensions (mm)

Code	Description	Value
H1	H1 — pump height	347
H2	H2 — motor height	345
H	H — overall height, flange	772
D1	D1 — motor diameter	197
D2	D2 — base / flange width	132
weight_cdmf_kg	Net weight CDMF	51
-	Net weight	53

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261027-181CE. Contact: +92 345 9547419 sales@cnppakistan.com