

CHLF(T)15-40

CHLF(T) | Horizontal multistage stainless steel centrifugal pump



CNP-M-001289

Scan to open this online



FLOW RANGE

10 - 26 m³/h

HEAD RANGE

48 - 73.5 m

MOTOR

5.5 kW

SPEED


3500 rpm

Specifications

Series	CHLF(T)
Size	CHLF15
Stages	4
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	5.5 kW (7.5 hp)
Max pressure	10 bar
Connection	Thread inlet G2, outlet G2
Weight	54 kg
Data basis	Published performance curve (Performance table printed pp. 51–52)

Performance curve

Head versus flow - CHLF(T)15-40, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
10	73.5
12	72.5
14	70.5
15	69.5



Flow (m³/h)	Head (m)
16	68.5
18	65.5
20	62
22	58
24	54
26	48

Dimensions (mm)

Code	Description	Value
L1	L1 — overall length, three-phase	646
L2	L2	349
L3	L3	216
N	N	132
E	E	242
A	A	248
M	M	216
B	B	184
J	J	140
d	d — bolt hole	12
D	D — motor width, three-phase	255
H	H — height, three-phase	300
-	Net weight	54

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-7370E. Contact: +92 345 9547419 sales@cnppakistan.com