

CHLF(T)4-50

CHLF(T) | Horizontal multistage stainless steel centrifugal pump



CNP-M-001475

Scan to open this online



FLOW RANGE

2 - 8 m³/h

HEAD RANGE

39 - 65.5 m

MOTOR

2.2 kW

SPEED


3500 rpm

Specifications

Series	CHLF(T)
Size	CHLF4
Stages	5
Mains frequency	60 Hz
Speed	3500 rpm
Motor power	2.2 kW (3 hp)
Max pressure	10 bar
Connection	Thread inlet G1¼, outlet G1
Weight	25 kg
Data basis	Published performance curve (Performance table printed pp. 45–46)

Performance curve

Head versus flow - CHLF(T)4-50, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
2	65.5
3	62.5
4	59
5	54.5



Flow (m³/h)	Head (m)
6	49
7	43
8	39

Dimensions (mm)

Code	Description	Value
L1	L1 — overall length, three-phase	492
L2	L2	186
L3	L3	183
N	N	118
E	E	190
D	D — motor width, three-phase	171
D_1ph	D — motor width, single-phase	176
H	H — height, three-phase	240
H_1ph	H — height, single-phase	260
K_1ph	K — single-phase only	91
-	Net weight	25

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-C7134. Contact: +92 345 9547419 sales@cnppakistan.com