

CHM15-60

CHM | Horizontal multistage stainless steel centrifugal pump



CNP-M-001165

Scan to open this online



FLOW RANGE

8 - 24 m³/h

HEAD RANGE

43 - 76 m

MOTOR

4.8 kW


SPEED

2900 rpm

Specifications

Series	CHM
Size	CHM15
Stages	60
Mains frequency	50 Hz
Speed	2900 rpm
Motor power	4.8 kW (6.5 hp)
Max pressure	10 bar
Connection	Thread G2
Weight	42 kg
Data basis	Published performance curve (Performance table printed p. 9; dimensions p. 12)

Performance curve



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
8	76
10	75
12	73
14	71



Flow (m³/h)	Head (m)
15	69
16	67
18	63
20	58
22	52
24	43

Dimensions (mm)

Code	Description	Value
L	L — overall length, three-phase	662
L1	L1, three-phase	401
L2	L2	273
L3	L3 — foot spacing	180
L4	L4	140
h	h — shaft axis height	112
H	H — height	230
G	G — overall height, three-phase	262
D	D — motor width, three-phase	214
M	M	190
P	P	230
d	d — bolt hole	12
-	Net weight	42

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-84C10. Contact: +92 345 9547419 sales@cnppakistan.com