CNP PUMPS PAKISTAN

SJ120-4-1

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump

CNP-M-001080

Scan to open this online

FLOW RANGE	HEAD RANGE	MOTOR	SPEED
60 - 150 m³/h	64 - 85 m	37 kW	2850 rpm

Specifications

Series	**SJ (deep-well submersible)**
Size	**SJ120**
Stages	**4**
Mains frequency	**50 Hz**
Speed	**2850 rpm**
Motor power	**37 kW (50 hp)**
Max pressure	**25 bar**
Connection	**Thread Rp6**
Variant	**1**
Data basis	**Published performance curve (Performance table, SJ size page (PDF p. 16))**

Performance curve



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m³/h)	Head (m)
60	85
70	84
80	82
90	79.5

Flow (m^3/h)	Head (m)
100	77
110	76
120	73.5
130	71
140	67
150	64

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261030-1EBEA. Contact: +92 345 9547419 sales@cnppakistan.com