

SJ17-3

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump



CNP-M-001613

Scan to open this online



FLOW RANGE

4 - 22 m³/h

HEAD RANGE

13 - 31 m

MOTOR

2.2 kW

SPEED


2850 rpm

Specifications

Series	SJ (deep-well submersible)
Size	SJ17
Stages	3
Mains frequency	50 Hz
Speed	2850 rpm
Motor power	2.2 kW (3 hp)
Max pressure	26 bar
Connection	Thread Rp2½
Data basis	Published performance curve (Performance table, SJ size page (PDF p. 10))

Performance curve

Head versus flow - SJ17-3, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
4	31
6	30
8	29.5
10	28.5
12	27



Flow (m³/h)	Head (m)
14	24.5
17	20.5
20	16
22	13

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-30429. Contact: +92 345 9547419 sales@cnppakistan.com