

SJ3-32

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump



CNP-M-001905

Scan to open this online



FLOW RANGE

0.8 - 4 m³/h

HEAD RANGE

79 - 189 m

MOTOR

2.2 kW

SPEED


2850 rpm

Specifications

Series	SJ (deep-well submersible)
Size	SJ3
Stages	32
Mains frequency	50 Hz
Speed	2850 rpm
Motor power	2.2 kW (3 hp)
Max pressure	25 bar
Connection	Thread Rp1¼
Data basis	Published performance curve (Performance table, SJ size page (PDF p. 6))

Performance curve

Head versus flow - SJ3-32, 50 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0.8	189
1.2	183
1.6	173
2.0	163
2.4	154



Flow (m³/h)	Head (m)
2.8	140
3	131
3.2	122
3.6	102
4	79

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261030-562D3. Contact: +92 345 9547419 sales@cnppakistan.com