CNP PUMPS PAKISTAN

SJ60-7

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump

CNP-M-001116

Scan to open this online

FLOW RANGE	HEAD RANGE	MOTOR	SPEED
20 - 75 m³/h	**30 - 92 m**	**13 kW**	**2850 rpm**

Specifications

Series	**SJ (deep-well submersible)**
Size	**SJ60**
Stages	**7**
Mains frequency	**50 Hz**
Speed	**2850 rpm**
Motor power	**13 kW (17.5 hp)**
Max pressure	**29 bar**
Connection	**Thread Rp4**
Data basis	**Published performance curve (Performance table, SJ size page (PDF p. 13))**

Performance curve



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m³/h)	Head (m)
20	92
30	84
40	73
50	63
60	53

Flow (m^3/h)	Head (m)
70	39
75	30

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-ED5BA. Contact: +92 345 9547419 sales@cnppakistan.com