

SJ1-35

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump



CNP-M-001869

Scan to open this online



FLOW RANGE

0.2 - 1.8 m³/h

HEAD RANGE

209 - 297 m

MOTOR

3 kW

SPEED


3450 rpm

Specifications

Series	SJ (deep-well submersible)
Size	SJ1
Stages	35
Mains frequency	60 Hz
Speed	3450 rpm
Motor power	3 kW (4 hp)
Max pressure	28 bar
Connection	Thread Rp1¼
Data basis	Published performance curve (Performance table, SJ 60 Hz size page (PDF p. 5))

Performance curve

Head versus flow - SJ1-35, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
0.2	297
0.4	295
0.6	291
0.8	285
1	277



Flow (m³/h)	Head (m)
1.2	267
1.4	252
1.6	234
1.8	209

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-B430B. Contact: +92 345 9547419 sales@cnppakistan.com