

SJ75-11

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump



CNP-M-001074

Scan to open this online



FLOW RANGE

40 - 120 m³/h

HEAD RANGE

135 - 292 m

MOTOR

75 kW

SPEED


3450 rpm

Specifications

Series	SJ (deep-well submersible)
Size	SJ75
Stages	11
Mains frequency	60 Hz
Speed	3450 rpm
Motor power	75 kW (100 hp)
Max pressure	38 bar
Connection	Thread Rp5
Data basis	Published performance curve (Performance table, SJ 60 Hz size page (PDF p. 14))

Performance curve

Head versus flow - SJ75-11, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
40	292
50	283
60	270
70	255
75	246



Flow (m³/h)	Head (m)
80	238
90	217
100	194
110	168
120	135

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261028-57EDF. Contact: +92 345 9547419 sales@cnppakistan.com