

SJ8-28

SJ (deep-well submersible) | Deep-well submersible multistage stainless steel pump



CNP-M-001750

Scan to open this online



FLOW RANGE

2 - 12 m³/h

HEAD RANGE

126 - 225 m

MOTOR

7.5 kW

SPEED


3450 rpm

Specifications

Series	SJ (deep-well submersible)
Size	SJ8
Stages	28
Mains frequency	60 Hz
Speed	3450 rpm
Motor power	7.5 kW (10 hp)
Max pressure	27 bar
Connection	Thread Rp2
Data basis	Published performance curve (Performance table, SJ 60 Hz size page (PDF p. 8))

Performance curve

Head versus flow - SJ8-28, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
2	225
3	219
4	213
5	206
6	199



Flow (m³/h)	Head (m)
7	192
8	184
9	176
10	164
11	148
12	126

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-D9E03. Contact: +92 345 9547419 sales@cnppakistan.com