

TD300-35/4

TD (in-line circulation) | In-line single-stage circulation pump



CNP-M-001789

Scan to open this online



FLOW RANGE

270 - 1200 m³/h

HEAD RANGE

26.3 - 40.6 m

MOTOR

132 kW

SPEED


1750 rpm

Specifications

Series	TD (in-line circulation)
Size	TD300
Mains frequency	60 Hz
Speed	1750 rpm
Motor power	132 kW
Max pressure	12 bar
Connection	Flange DN300 (PN16)
Weight	1540 kg
Data basis	Published performance curve (Performance table, PDF p. 37)

Performance curve

Head versus flow - TD300-35/4, 60 Hz



Efficiency, shaft power and NPSHr are not published for this model in the source catalogue.

Performance table

Flow (m ³ /h)	Head (m)
270	40.6
360	40
450	39.6
630	38.2
750	37



Flow (m³/h)	Head (m)
900	35
1080	30.2
1200	26.3

Dimensions (mm)

Code	Description	Value
D	D	660
B1	B1	625
B2	B2	555
B3	B3	345
B4	B4	250
B5	B5	440
H1	H1	290
H2	H2	679
H3	H3	2150
L1	L1	1200
L2	L2	600
-	Net weight	1540

Dimension codes follow the CNP catalogue drawing. Confirm installation dimensions with the approved drawing before civil or piping work.

Performance is for clean water at 20 °C unless stated, per the CNP published catalogue. Tolerances follow ISO 9906. This datasheet is for selection guidance; final selection, materials and price are confirmed in our written quotation. Reference SR-261029-85439. Contact: +92 345 9547419 sales@cnppakistan.com