

CM

Model & performance table



CNP-S-000090

Scan to open this online



Light horizontal multistage centrifugal pumps, CM

Models (23)

Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
CM2-2 (50)	0.37	2900	0.5 - 3.5	19 - 7.5	7
CM2-3 (50)	0.37	2900	0.5 - 3.5	28 - 12	7
CM2-4 (50)	0.55	2900	0.5 - 3.5	36 - 16	9
CM2-5 (50)	0.55	2900	0.5 - 3.5	45.5 - 20.5	9.5
CM2-6 (50)	0.75	2900	0.5 - 3.5	53.5 - 24	10
CM4-2 (50)	0.37	2900	1 - 7	19 - 8	7
CM4-3 (50)	0.55	2900	1 - 7	28 - 13	9
CM4-4 (50)	0.75	2900	1 - 7	37.5 - 19	10
CM4-5 (50)	1.1	2900	1 - 7	47 - 23	13
CM4-6 (50)	1.1	2900	1 - 7	56 - 28	13
CM10-1 (50)	0.75	2900	5 - 14	10.2 - 4.5	11.5
CM10-2 (50)	0.75	2900	5 - 14	21 - 9.5	11.5
CM10-3 (50)	1.1	2900	5 - 14	31.5 - 16.5	14
CM10-4 (50)	1.5	2900	5 - 14	42 - 22	18
CM10-5 (50)	2.2	2900	5 - 14	52.5 - 28	21
CM15-1 (50)	1.1	2900	8 - 24	12.2 - 6.5	13.5
CM15-2 (50)	2.2	2900	8 - 24	24.5 - 13.5	19.5
CM15-3 (50)	3	2900	8 - 24	37.5 - 21	27
CM15-4 (50)	4	2900	8 - 24	50.5 - 28.5	35.5
CM20-1 (50)	1.1	2900	10 - 29	12.5 - 7	13.5
CM20-2 (50)	2.2	2900	10 - 29	25.5 - 14.5	19.5
CM20-3 (50)	3	2900	10 - 29	39.5 - 23.5	28.5
CM20-4 (50)	4	2900	10 - 29	52.5 - 31.5	37

Performance is for clean water at 20 C unless stated, as published in the CNP catalogue. The ranges show the first and last points of each performance curve. For a datasheet with the full curve and dimensions, open the model page.