

QZB axial-flow

Model & performance table



CNP-S-000015

Scan to open this online



Axial / mixed-flow submersible pump, QZB submersible axial-flow pump

Models (99)

Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
350QZB-50	45	1450	-	-	-
350QZB-50J	15	980	-	-	-
350QZB-70	30	1450	-	-	-
350QZB-70J	7.5	980	-	-	-
350QZB-70*	45	1450	-	-	-
350QZB-70*J	15	980	-	-	-
350QZB-85	37	1450	-	-	-
350QZB-85J	11	980	-	-	-
350QZB-100	30	1450	-	-	-
350QZB-100J	11	980	-	-	-
350QZB-125	22	1450	-	-	-
350QZB-125J	7.5	980	-	-	-
350QZB-160	18.5	1450	-	-	-
350QZB-160J	7.5	980	-	-	-
500QZB-50	110	980	-	-	-
500QZB-50J	45	730	-	-	-
500QZB-70	55	980	-	-	-
500QZB-70J	30	730	-	-	-
500QZB-70*	110	980	-	-	-
500QZB-70*J	45	730	-	-	-
500QZB-85	65	980	-	-	-
500QZB-85J	30	730	-	-	-
500QZB-100	55	980	-	-	-
500QZB-100J	30	730	-	-	-
500QZB-125	55	980	-	-	-
500QZB-125J	22	730	-	-	-
500QZB-160	45	980	-	-	-
500QZB-160J	15	730	-	-	-
600QZB-50	110	730	-	-	-
600QZB-70	65	730	-	-	-
600QZB-70*	110	730	-	-	-
600QZB-75	110	740	-	-	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
600QZB-85	80	730	-	-	-
600QZB-100	65	730	-	-	-
600QZB-125	65	730	-	-	-
600QZB-160	45	730	-	-	-
700QZB-50	250	730	-	-	-
700QZB-50J	132	590	-	-	-
700QZB-70	155	730	-	-	-
700QZB-70J	80	590	-	-	-
700QZB-70*	280	730	-	-	-
700QZB-70*J	132	590	-	-	-
700QZB-85	155	730	-	-	-
700QZB-100	155	730	-	-	-
700QZB-100J	80	590	-	-	-
700QZB-125	132	730	-	-	-
700QZB-125J	80	590	-	-	-
700QZB-160	95	730	-	-	-
700QZB-160J	65	590	-	-	-
800QZB-50	310	590	-	-	-
800QZB-50J	155	490	-	-	-
800QZB-70	155	590	-	-	-
800QZB-70*	280	590	-	-	-
800QZB-70*J	155	490	-	-	-
800QZB-85	180	590	-	-	-
800QZB-85J	110	490	-	-	-
800QZB-100	155	590	-	-	-
800QZB-100J	90	490	-	-	-
800QZB-125	155	590	-	-	-
800QZB-125J	90	490	-	-	-
800QZB-160	110	590	-	-	-
800QZB-160J	65	490	-	-	-
900QZB-50	310	490	-	-	-
900QZB-50J	250	490	-	-	-
900QZB-70	180	490	-	-	-
900QZB-70J	250	590	-	-	-
900QZB-70*	280	490	-	-	-
900QZB-85	200	490	-	-	-
900QZB-100	155	490	-	-	-
900QZB-100T	310	590	-	-	-
900QZB-125	155	490	-	-	-
900QZB-160	110	490	-	-	-
1000QZB-50	355	490	-	-	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
1000QZB-70	280	490	-	-	-
1000QZB-100	185	490	-	-	-
1000QZB-125	160	490	-	-	-
1200QZB-50	560	490	-	-	-
1200QZB-70	450	490	-	-	-
1200QZB-100	280	490	-	-	-
1200QZB-125	250	490	-	-	-
1200QZB-160	185	490	-	-	-
1400QZB-70	550	365	-	-	-
1400QZB-100	500	370	-	-	-
1400QZB-125	400	365	-	-	-
1600QZB-70	900	295	-	-	-
1600QZB-100	560	295	-	-	-
1600QZB-125	500	295	-	-	-
1600QZB-160	355	295	-	-	-
1800QZB-70	800	257	-	-	-
1800QZB-70*	1000	230	-	-	-
1800QZB-85	900	257	-	-	-
1800QZB-100	800	257	-	-	-
1800QZB-125	710	257	-	-	-
1800QZB-160	500	257	-	-	-
2000QZB-70	1000	215	-	-	-
2000QZB-85	1100	215	-	-	-
2000QZB-100	900	215	-	-	-
2000QZB-125	800	215	-	-	-
2000QZB-160	630	215	-	-	-

Performance is for clean water at 20 C unless stated, as published in the CNP catalogue. The ranges show the first and last points of each performance curve. For a datasheet with the full curve and dimensions, open the model page.