

SJ (deep-well submersible)

Model & performance table



CNP-S-000021

Scan to open this online



Stainless steel deep-well submersible multistage pumps, SJ

Models (436)

Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ1-6 (50)	0.37	2850	0.2 - 2	33.5 - 19	-
SJ1-9 (50)	0.37	2850	0.2 - 2	51 - 29	-
SJ1-13 (50)	0.55	2850	0.2 - 2	73 - 42	-
SJ1-17 (50)	0.75	2850	0.2 - 2	96 - 55	-
SJ1-21 (50)	1.1	2850	0.2 - 2	119 - 69	-
SJ1-25 (50)	1.1	2850	0.2 - 2	141 - 82	-
SJ1-28 (50)	1.5	2850	0.2 - 2	158 - 92	-
SJ1-32 (50)	1.5	2850	0.2 - 2	180 - 105	-
SJ1-36 (50)	1.5	2850	0.2 - 2	203 - 118	-
SJ1-39 (50)	2.2	2850	0.2 - 2	221 - 128	-
SJ1-42 (50)	2.2	2850	0.2 - 2	238 - 137	-
SJ1-46 (50)	2.2	2850	0.2 - 2	260 - 151	-
SJ1-50 (50)	2.2	2850	0.2 - 2	284 - 165	-
SJ3-6 (50)	0.37	2850	0.8 - 4	36 - 13	-
SJ3-9 (50)	0.55	2850	0.8 - 4	53 - 20	-
SJ3-12 (50)	0.75	2850	0.8 - 4	70 - 27	-
SJ3-15 (50)	1.1	2850	0.8 - 4	87 - 34	-
SJ3-18 (50)	1.1	2850	0.8 - 4	105 - 42	-
SJ3-22 (50)	1.5	2850	0.8 - 4	130 - 53	-
SJ3-27 (50)	2.2	2850	0.8 - 4	159 - 66	-
SJ3-32 (50)	2.2	2850	0.8 - 4	189 - 79	-
SJ3-38 (50)	3	2850	0.8 - 4	224 - 94	-
SJ3-43 (50)	3	2850	0.8 - 4	254 - 107	-
SJ5-4 (50)	0.37	2850	1 - 6.5	21 - 8	-
SJ5-6 (50)	0.55	2850	1 - 6.5	32 - 11	-
SJ5-8 (50)	0.75	2850	1 - 6.5	43 - 15	-
SJ5-12 (50)	1.1	2850	1 - 6.5	66 - 23	-
SJ5-17 (50)	1.5	2850	1 - 6.5	95 - 32	-
SJ5-21 (50)	2.2	2850	1 - 6.5	117 - 39	-
SJ5-25 (50)	2.2	2850	1 - 6.5	139 - 47	-
SJ5-29 (50)	3	2850	1 - 6.5	161 - 55	-
SJ5-33 (50)	3	2850	1 - 6.5	183 - 62	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ5-38 (50)	4	2850	1 - 6.5	211 - 71	-
SJ5-43 (50)	4	2850	1 - 6.5	239 - 81	-
SJ8-5 (50)	0.75	2850	2 - 11	27 - 10	-
SJ8-7 (50)	1.1	2850	2 - 11	38 - 14	-
SJ8-10 (50)	1.5	2850	2 - 11	54 - 21	-
SJ8-12 (50)	2.2	2850	2 - 11	65 - 26	-
SJ8-15 (50)	2.2	2850	2 - 11	81 - 33	-
SJ8-18 (50)	3	2850	2 - 11	95 - 40	-
SJ8-21 (50)	4	2850	2 - 11	112 - 47	-
SJ8-25 (50)	4	2850	2 - 11	135 - 56	-
SJ8-30 (50)	5.5	2850	2 - 11	162 - 67	-
SJ8-37 (50)	5.5	2850	2 - 11	201 - 82	-
SJ8-44 (50)	7.5	2850	2 - 11	242 - 98	-
SJ8-50 (50)	7.5	2850	2 - 11	272 - 111	-
SJ12-5 (50)	1.5	2850	3 - 18	34 - 13	-
SJ12-7 (50)	2.2	2850	3 - 18	48 - 19	-
SJ12-10 (50)	3	2850	3 - 18	67 - 27	-
SJ12-13 (50)	4	2850	3 - 18	88 - 36	-
SJ12-15 (50)	5.5	2850	3 - 18	99 - 41	-
SJ12-18 (50)	5.5	2850	3 - 18	120 - 50	-
SJ12-21 (50)	7.5	2850	3 - 18	138 - 58	-
SJ12-25 (50)	7.5	2850	3 - 18	166 - 69	-
SJ17-1 (50)	0.55	2850	4 - 22	10.5 - 4	-
SJ17-2 (50)	1.1	2850	4 - 22	20.5 - 8	-
SJ17-3 (50)	2.2	2850	4 - 22	31 - 13	-
SJ17-4 (50)	2.2	2850	4 - 22	41 - 18	-
SJ17-5 (50)	3	2850	4 - 22	52 - 23	-
SJ17-6 (50)	4	2850	4 - 22	62 - 27	-
SJ17-7 (50)	4	2850	4 - 22	73 - 31	-
SJ17-8 (50)	5.5	2850	4 - 22	83 - 36	-
SJ17-9 (50)	5.5	2850	4 - 22	93 - 40	-
SJ17-10 (50)	5.5	2850	4 - 22	103 - 45	-
SJ17-11 (50)	7.5	2850	4 - 22	113 - 50	-
SJ17-12 (50)	7.5	2850	4 - 22	123 - 55	-
SJ17-13 (50)	7.5	2850	4 - 22	133 - 60	-
SJ17-14 (50)	9.2	2850	4 - 22	143 - 65	-
SJ17-15 (50)	9.2	2850	4 - 22	153 - 70	-
SJ17-16 (50)	9.2	2850	4 - 22	163 - 75	-
SJ17-17 (50)	9.2	2850	4 - 22	173 - 79	-
SJ17-18 (50)	11	2850	4 - 22	184 - 84	-
SJ17-19 (50)	11	2850	4 - 22	194 - 89	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ17-20 (50)	11	2850	4 - 22	204 - 94	-
SJ17-21 (50)	13	2850	4 - 22	214 - 99	-
SJ17-22 (50)	13	2850	4 - 22	224 - 104	-
SJ17-23 (50)	13	2850	4 - 22	235 - 109	-
SJ17-24 (50)	13	2850	4 - 22	245 - 113	-
SJ17-25 (50)	15	2850	4 - 22	255 - 118	-
SJ17-26 (50)	15	2850	4 - 22	265 - 122	-
SJ30-1 (50)	1.1	2850	5 - 38	11.5 - 4.5	-
SJ30-2 (50)	2.2	2850	5 - 38	22.5 - 9	-
SJ30-3 (50)	3	2850	5 - 38	33.5 - 14	-
SJ30-4 (50)	4	2850	5 - 38	44.5 - 18	-
SJ30-5 (50)	5.5	2850	5 - 38	55.5 - 23	-
SJ30-6 (50)	5.5	2850	5 - 38	67 - 27	-
SJ30-7 (50)	7.5	2850	5 - 38	77 - 32	-
SJ30-8 (50)	7.5	2850	5 - 38	89 - 36	-
SJ30-9 (50)	9.2	2850	5 - 38	101 - 41	-
SJ30-10 (50)	9.2	2850	5 - 38	112 - 45	-
SJ30-11 (50)	9.2	2850	5 - 38	123 - 50	-
SJ30-12 (50)	11	2850	5 - 38	134 - 54	-
SJ30-13 (50)	11	2850	5 - 38	145 - 59	-
SJ30-14 (50)	13	2850	5 - 38	157 - 63	-
SJ30-15 (50)	13	2850	5 - 38	168 - 68	-
SJ30-16 (50)	15	2850	5 - 38	180 - 72	-
SJ30-17 (50)	15	2850	5 - 38	190 - 77	-
SJ30-18 (50)	18.5	2850	5 - 38	201 - 81	-
SJ30-19 (50)	18.5	2850	5 - 38	212 - 86	-
SJ30-20 (50)	18.5	2850	5 - 38	223 - 90	-
SJ30-21 (50)	18.5	2850	5 - 38	235 - 95	-
SJ30-22 (50)	22	2850	5 - 38	246 - 99	-
SJ30-23 (50)	22	2850	5 - 38	258 - 104	-
SJ30-24 (50)	22	2850	5 - 38	269 - 108	-
SJ30-25 (50)	22	2850	5 - 38	281 - 113	-
SJ42-1 (50)	2.2	2850	5 - 60	13 - 4	-
SJ42-2 (50)	3	2850	5 - 60	26 - 8.5	-
SJ42-3 (50)	5.5	2850	5 - 60	40 - 13	-
SJ42-4 (50)	7.5	2850	5 - 60	53 - 18	-
SJ42-5 (50)	7.5	2850	5 - 60	66 - 23	-
SJ42-6 (50)	9.2	2850	5 - 60	79 - 28	-
SJ42-7 (50)	11	2850	5 - 60	92 - 32	-
SJ42-8 (50)	13	2850	5 - 60	105 - 36	-
SJ42-9 (50)	15	2850	5 - 60	118 - 40	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ42-10 (50)	15	2850	5 - 60	132 - 45	-
SJ42-11 (50)	18.5	2850	5 - 60	144 - 49	-
SJ42-12 (50)	18.5	2850	5 - 60	157 - 54	-
SJ42-13 (50)	22	2850	5 - 60	170 - 58	-
SJ42-14 (50)	22	2850	5 - 60	183 - 63	-
SJ42-15 (50)	22	2850	5 - 60	196 - 67	-
SJ42-16 (50)	25	2850	5 - 60	209 - 72	-
SJ42-17 (50)	25	2850	5 - 60	222 - 77	-
SJ42-18 (50)	30	2850	5 - 60	235 - 81	-
SJ42-19 (50)	30	2850	5 - 60	248 - 86	-
SJ42-20 (50)	30	2850	5 - 60	261 - 90	-
SJ42-21 (50)	37	2850	5 - 60	274 - 95	-
SJ42-22 (50)	37	2850	5 - 60	287 - 99	-
SJ60-1 (50)	2.2	2850	20 - 70	12 - 4	-
SJ60-2-2 (50)	3	2850	20 - 75	20 - 4	-
SJ60-2 (50)	4	2850	20 - 75	24.5 - 6	-
SJ60-3 (50)	5.5	2850	20 - 75	37 - 10	-
SJ60-4 (50)	7.5	2850	20 - 75	51 - 17	-
SJ60-5 (50)	9.2	2850	20 - 75	65 - 21	-
SJ60-6 (50)	11	2850	20 - 75	79 - 26	-
SJ60-7 (50)	13	2850	20 - 75	92 - 30	-
SJ60-8-2 (50)	13	2850	20 - 75	99 - 31	-
SJ60-8 (50)	15	2850	20 - 75	105 - 35	-
SJ60-9-2 (50)	15	2850	20 - 75	112 - 36	-
SJ60-9 (50)	18.5	2850	20 - 75	121 - 40	-
SJ60-10 (50)	18.5	2850	20 - 75	132 - 45	-
SJ60-11 (50)	22	2850	20 - 75	145 - 50	-
SJ60-12 (50)	22	2850	20 - 75	158 - 54	-
SJ60-13 (50)	25	2850	20 - 75	172 - 59	-
SJ60-14 (50)	25	2850	20 - 75	185 - 63	-
SJ60-15 (50)	30	2850	20 - 75	198 - 68	-
SJ60-16 (50)	30	2850	20 - 75	212 - 72	-
SJ60-17 (50)	30	2850	20 - 75	224 - 77	-
SJ60-18 (50)	37	2850	20 - 75	240 - 84	-
SJ60-19 (50)	37	2850	20 - 75	253 - 89	-
SJ60-20 (50)	37	2850	20 - 75	265 - 94	-
SJ60-21 (50)	37	2850	20 - 75	278 - 98	-
SJ75-1 (50)	4	2850	30 - 100	18 - 5.5	-
SJ75-2 (50)	7.5	2850	30 - 100	36.5 - 12.5	-
SJ75-3 (50)	11	2850	30 - 100	54.5 - 21.5	-
SJ75-4 (50)	15	2850	30 - 100	73.5 - 30	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ75-5 (50)	18.5	2850	30 - 100	92 - 38	-
SJ75-6 (50)	22	2850	30 - 100	111 - 47	-
SJ75-7 (50)	30	2850	30 - 100	130 - 56	-
SJ75-8 (50)	30	2850	30 - 100	148 - 65	-
SJ75-9 (50)	37	2850	30 - 100	167 - 74	-
SJ75-10 (50)	37	2850	30 - 100	185 - 83	-
SJ75-11 (50)	45	2850	30 - 100	203 - 92	-
SJ75-12 (50)	45	2850	30 - 100	222 - 100	-
SJ75-13 (50)	55	2850	30 - 100	241 - 108	-
SJ75-14 (50)	55	2850	30 - 100	262 - 116	-
SJ75-15 (50)	55	2850	30 - 100	283 - 124	-
SJ75-16 (50)	63	2850	30 - 100	303 - 133	-
SJ75-17 (50)	63	2850	30 - 100	323 - 142	-
SJ75-18 (50)	75	2850	30 - 100	342 - 150	-
SJ75-19 (50)	75	2850	30 - 100	361 - 158	-
SJ75-20 (50)	75	2850	30 - 100	381 - 167	-
SJ95-1 (50)	4	2850	40 - 110	17.5 - 5	-
SJ95-2 (50)	9.2	2850	40 - 120	36 - 3.5	-
SJ95-3 (50)	13	2850	40 - 120	54 - 6	-
SJ95-4 (50)	18.5	2850	40 - 120	72 - 10.5	-
SJ95-5 (50)	22	2850	40 - 120	91 - 14.5	-
SJ95-6 (50)	25	2850	40 - 120	110 - 18	-
SJ95-7 (50)	30	2850	40 - 120	129 - 22	-
SJ95-8 (50)	37	2850	40 - 120	148 - 26	-
SJ95-9 (50)	37	2850	40 - 120	167 - 31	-
SJ95-10 (50)	45	2850	40 - 120	186 - 36	-
SJ95-11 (50)	45	2850	40 - 120	205 - 42	-
SJ95-12 (50)	55	2850	40 - 120	224 - 48	-
SJ95-13 (50)	55	2850	40 - 120	243 - 53	-
SJ95-14 (50)	55	2850	40 - 120	262 - 59	-
SJ95-15 (50)	63	2850	40 - 120	281 - 64	-
SJ95-16 (50)	63	2850	40 - 120	301 - 70	-
SJ95-17 (50)	75	2850	40 - 120	321 - 75	-
SJ95-18 (50)	75	2850	40 - 120	342 - 81	-
SJ120-1 (50)	11	2850	60 - 150	22.5 - 16.5	-
SJ120-2-2 (50)	15	2850	60 - 150	33.5 - 24	-
SJ120-2-1 (50)	18.5	2850	60 - 150	40.5 - 28	-
SJ120-2 (50)	22	2850	60 - 150	45.5 - 34	-
SJ120-3-2 (50)	25	2850	60 - 150	55 - 40.5	-
SJ120-3-1 (50)	30	2850	60 - 150	62.5 - 46	-
SJ120-3 (50)	30	2850	60 - 150	68 - 51	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ120-4-2 (50)	37	2850	60 - 150	78.5 - 57.5	-
SJ120-4-1 (50)	37	2850	60 - 150	85 - 64	-
SJ120-4 (50)	37	2850	60 - 150	90.5 - 68	-
SJ120-5-2 (50)	45	2850	60 - 150	102 - 74.5	-
SJ120-5-1 (50)	45	2850	60 - 150	108.5 - 82	-
SJ120-5 (50)	55	2850	60 - 150	113.5 - 85	-
SJ120-6-2 (50)	55	2850	60 - 150	125 - 90.5	-
SJ120-6-1 (50)	55	2850	60 - 150	131 - 98	-
SJ120-6 (50)	63	2850	60 - 150	136 - 102	-
SJ120-7-2 (50)	63	2850	60 - 150	147 - 106	-
SJ120-7-1 (50)	63	2850	60 - 150	153 - 112.5	-
SJ120-7 (50)	75	2850	60 - 150	159 - 119.5	-
SJ120-8-2 (50)	75	2850	60 - 150	170 - 123	-
SJ120-8-1 (50)	75	2850	60 - 150	175.5 - 129.5	-
SJ120-8 (50)	75	2850	60 - 150	181.5 - 136.5	-
SJ120-9-2 (50)	90	2850	60 - 150	192.5 - 140	-
SJ120-9-1 (50)	90	2850	60 - 150	198 - 147	-
SJ120-9 (50)	90	2850	60 - 150	204 - 153.5	-
SJ120-10-2 (50)	90	2850	60 - 150	215.5 - 157.5	-
SJ120-10-1 (50)	90	2850	60 - 150	221 - 164	-
SJ120-10 (50)	110	2850	60 - 150	227 - 170.5	-
SJ120-11-2 (50)	110	2850	60 - 150	238 - 174.5	-
SJ120-11-1 (50)	110	2850	60 - 150	243.5 - 181	-
SJ120-11 (50)	110	2850	60 - 150	250 - 187.5	-
SJ150-1-1 (50)	9.2	2850	80 - 180	18.5 - 11.5	-
SJ150-1 (50)	13	2850	80 - 180	24 - 18	-
SJ150-2-2 (50)	18.5	2850	80 - 180	35.5 - 25	-
SJ150-2-1 (50)	22	2850	80 - 180	43 - 31	-
SJ150-2 (50)	25	2850	80 - 180	48.5 - 36	-
SJ150-3-2 (50)	30	2850	80 - 180	60 - 43	-
SJ150-3-1 (50)	37	2850	80 - 180	66.5 - 49	-
SJ150-3 (50)	37	2850	80 - 180	74.5 - 54.5	-
SJ150-4-2 (50)	45	2850	80 - 180	85.5 - 61	-
SJ150-4-1 (50)	45	2850	80 - 180	93 - 67	-
SJ150-4 (50)	55	2850	80 - 180	100.5 - 73	-
SJ150-5-2 (50)	55	2850	80 - 180	111.5 - 78.5	-
SJ150-5-1 (50)	55	2850	80 - 180	118.5 - 85	-
SJ150-5 (50)	63	2850	80 - 180	126 - 91.5	-
SJ150-6-2 (50)	63	2850	80 - 180	137 - 97	-
SJ150-6-1 (50)	75	2850	80 - 180	144 - 103.5	-
SJ150-6 (50)	75	2850	80 - 180	151.5 - 110	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ150-7-2 (50)	75	2850	80 - 180	162.5 - 115	-
SJ150-7-1 (50)	90	2850	80 - 180	169.5 - 121.5	-
SJ150-7 (50)	90	2850	80 - 180	177 - 128	-
SJ150-8-2 (50)	90	2850	80 - 180	188 - 133.5	-
SJ150-8-1 (50)	110	2850	80 - 180	195 - 140	-
SJ150-8 (50)	110	2850	80 - 180	202.5 - 146.5	-
SJ150-9-2 (50)	110	2850	80 - 180	213.5 - 152	-
SJ150-9-1 (50)	110	2850	80 - 180	220.5 - 158.5	-
SJ150-9 (50)	110	2850	80 - 180	228 - 165	-
SJ200-1 (50)	30	2850	100 - 240	37 - 29	-
SJ200-2-2B (50)	37	2850	100 - 240	51 - 31	-
SJ200-2-2A (50)	45	2850	100 - 240	57.5 - 39	-
SJ200-2-A (50)	55	2850	100 - 240	66.5 - 49.5	-
SJ200-2 (50)	55	2850	100 - 240	76 - 59.5	-
SJ200-3-2B (50)	75	2850	100 - 240	88.5 - 63	-
SJ200-3-A-B (50)	75	2850	100 - 240	92 - 65	-
SJ200-3-2A (50)	75	2850	100 - 240	96 - 69.5	-
SJ200-3-B (50)	75	2850	100 - 240	101 - 75	-
SJ200-3-A (50)	75	2850	100 - 240	104.5 - 79	-
SJ200-3 (50)	90	2850	100 - 240	113.5 - 89	-
SJ200-4-2B (50)	90	2850	100 - 240	127 - 91	-
SJ200-4-2A (50)	110	2850	100 - 240	134 - 99	-
SJ200-4-A (50)	110	2850	100 - 240	143 - 109.5	-
SJ200-4 (50)	110	2850	100 - 240	152 - 117	-
SJ1-4 (60)	0.37	3450	0.2 - 1.8	33 - 22.5	-
SJ1-7 (60)	0.55	3450	0.2 - 1.8	58.5 - 41	-
SJ1-10 (60)	0.75	3450	0.2 - 1.8	85 - 59	-
SJ1-15 (60)	1.1	3450	0.2 - 1.8	127 - 89	-
SJ1-20 (60)	1.5	3450	0.2 - 1.8	170 - 119	-
SJ1-25 (60)	2.2	3450	0.2 - 1.8	213 - 149	-
SJ1-29 (60)	2.2	3450	0.2 - 1.8	247 - 172	-
SJ1-35 (60)	3	3450	0.2 - 1.8	297 - 209	-
SJ3-3 (60)	0.37	3450	0.6 - 4.6	25 - 9	-
SJ3-5 (60)	0.55	3450	0.6 - 4.6	43 - 16	-
SJ3-7 (60)	0.75	3450	0.6 - 4.6	60 - 23	-
SJ3-10 (60)	1.1	3450	0.6 - 4.6	86 - 33	-
SJ3-14 (60)	1.5	3450	0.6 - 4.6	121 - 46	-
SJ3-19 (60)	2.2	3450	0.6 - 4.6	164 - 63	-
SJ3-23 (60)	3	3450	0.6 - 4.6	199 - 76	-
SJ3-27 (60)	3	3450	0.6 - 4.6	233 - 89	-
SJ3-33 (60)	4	3450	0.6 - 4.6	286 - 110	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ5-3 (60)	0.55	3450	1 - 7.5	24 - 8.5	-
SJ5-5 (60)	0.75	3450	1 - 7.5	41 - 15.5	-
SJ5-7 (60)	1.1	3450	1 - 7.5	57 - 22	-
SJ5-10 (60)	1.5	3450	1 - 7.5	83 - 31	-
SJ5-14 (60)	2.2	3450	1 - 7.5	116 - 44	-
SJ5-19 (60)	3	3450	1 - 7.5	158 - 60	-
SJ5-22 (60)	4	3450	1 - 7.5	183 - 69	-
SJ5-26 (60)	4	3450	1 - 7.5	216 - 82	-
SJ5-34 (60)	5.5	3450	1 - 7.5	282 - 107	-
SJ8-3 (60)	1.1	3450	2 - 12	24 - 13.5	-
SJ8-4 (60)	1.1	3450	2 - 12	32 - 18	-
SJ8-5 (60)	1.5	3450	2 - 12	40 - 22.5	-
SJ8-7 (60)	2.2	3450	2 - 12	56 - 32	-
SJ8-8 (60)	2.2	3450	2 - 12	64 - 36	-
SJ8-9 (60)	3	3450	2 - 12	72 - 41	-
SJ8-11 (60)	3	3450	2 - 12	88 - 50	-
SJ8-12 (60)	4	3450	2 - 12	97 - 54	-
SJ8-15 (60)	4	3450	2 - 12	121 - 68	-
SJ8-18 (60)	5.5	3450	2 - 12	147 - 81	-
SJ8-21 (60)	5.5	3450	2 - 12	171 - 95	-
SJ8-25 (60)	7.5	3450	2 - 12	201 - 113	-
SJ8-28 (60)	7.5	3450	2 - 12	225 - 126	-
SJ12-3 (60)	2.2	3450	4 - 21	27 - 12	-
SJ12-4 (60)	2.2	3450	4 - 21	36 - 16.5	-
SJ12-5 (60)	3	3450	4 - 21	45 - 21	-
SJ12-7 (60)	4	3450	4 - 21	63 - 28	-
SJ12-8 (60)	5.5	3450	4 - 21	72 - 32	-
SJ12-10 (60)	5.5	3450	4 - 21	90 - 40	-
SJ12-12 (60)	7.5	3450	4 - 21	108 - 49	-
SJ12-14 (60)	7.5	3450	4 - 21	126 - 57	-
SJ17-1 (60)	1.1	3450	4 - 26	14 - 5	-
SJ17-2 (60)	2.2	3450	4 - 26	28 - 11.5	-
SJ17-3 (60)	3	3450	4 - 26	44 - 19	-
SJ17-4 (60)	4	3450	4 - 26	60 - 26	-
SJ17-5 (60)	5.5	3450	4 - 26	75 - 33	-
SJ17-6 (60)	7.5	3450	4 - 26	90 - 40	-
SJ17-7 (60)	7.5	3450	4 - 26	106 - 48	-
SJ17-8 (60)	9.2	3450	4 - 26	121 - 55	-
SJ17-9 (60)	9.2	3450	4 - 26	137 - 62	-
SJ17-10 (60)	11	3450	4 - 26	153 - 69	-
SJ17-11 (60)	11	3450	4 - 26	168 - 76	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ17-12 (60)	13	3450	4 - 26	183 - 84	-
SJ17-13 (60)	13	3450	4 - 26	199 - 91	-
SJ17-14 (60)	15	3450	4 - 26	214 - 98	-
SJ17-15 (60)	15	3450	4 - 26	229 - 105	-
SJ17-16 (60)	18.5	3450	4 - 26	244 - 112	-
SJ17-17 (60)	18.5	3450	4 - 26	260 - 119	-
SJ17-18 (60)	18.5	3450	4 - 26	275 - 126	-
SJ30-1 (60)	1.5	3450	8 - 46	16 - 4.5	-
SJ30-2 (60)	3	3450	8 - 46	32 - 11.5	-
SJ30-3 (60)	5.5	3450	8 - 46	48 - 17.5	-
SJ30-4 (60)	7.5	3450	8 - 46	64 - 25	-
SJ30-5 (60)	7.5	3450	8 - 46	81 - 31	-
SJ30-6 (60)	9.2	3450	8 - 46	97 - 39	-
SJ30-7 (60)	11	3450	8 - 46	113 - 45	-
SJ30-8 (60)	13	3450	8 - 46	129 - 52	-
SJ30-9 (60)	15	3450	8 - 46	145 - 58	-
SJ30-10 (60)	15	3450	8 - 46	162 - 65	-
SJ30-11 (60)	18.5	3450	8 - 46	178 - 71	-
SJ30-12 (60)	18.5	3450	8 - 46	195 - 77	-
SJ30-13 (60)	22	3450	8 - 46	211 - 84	-
SJ30-14 (60)	22	3450	8 - 46	227 - 90	-
SJ30-15 (60)	25	3450	8 - 46	244 - 97	-
SJ30-16 (60)	25	3450	8 - 46	260 - 103	-
SJ30-17 (60)	25	3450	8 - 46	276 - 110	-
SJ42-1 (60)	3	3450	10 - 70	17 - 5	-
SJ42-2 (60)	5.5	3450	10 - 70	36 - 12.5	-
SJ42-3 (60)	9.2	3450	10 - 70	55 - 20	-
SJ42-4 (60)	11	3450	10 - 70	74 - 27	-
SJ42-5 (60)	13	3450	10 - 70	93 - 35	-
SJ42-6 (60)	18.5	3450	10 - 70	111 - 43	-
SJ42-7 (60)	18.5	3450	10 - 70	131 - 50	-
SJ42-8 (60)	22	3450	10 - 70	150 - 56	-
SJ42-9 (60)	25	3450	10 - 70	168 - 64	-
SJ42-10 (60)	30	3450	10 - 70	187 - 72	-
SJ42-11 (60)	30	3450	10 - 70	206 - 79	-
SJ42-12 (60)	37	3450	10 - 70	225 - 87	-
SJ42-13 (60)	37	3450	10 - 70	244 - 94	-
SJ42-14 (60)	37	3450	10 - 70	263 - 101	-
SJ60-1 (60)	4	3450	10 - 90	19 - 3	-
SJ60-2 (60)	7.5	3450	10 - 90	39 - 8.5	-
SJ60-3-2 (60)	7.5	3450	10 - 90	49 - 8.5	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ60-3 (60)	9.2	3450	10 - 90	60 - 16	-
SJ60-4 (60)	13	3450	10 - 90	80 - 23	-
SJ60-5 (60)	15	3450	10 - 90	100 - 31	-
SJ60-6 (60)	18.5	3450	10 - 90	120 - 38	-
SJ60-7 (60)	22	3450	10 - 90	140 - 44	-
SJ60-8-2 (60)	22	3450	10 - 90	152 - 44	-
SJ60-8 (60)	25	3450	10 - 90	161 - 51	-
SJ60-9-2 (60)	25	3450	10 - 90	172 - 51	-
SJ60-9 (60)	30	3450	10 - 90	181 - 58	-
SJ60-10 (60)	30	3450	10 - 90	202 - 65	-
SJ60-11 (60)	37	3450	10 - 90	223 - 71	-
SJ60-12 (60)	37	3450	10 - 90	244 - 77	-
SJ75-1 (60)	7.5	3450	40 - 120	25 - 8	-
SJ75-2 (60)	13	3450	40 - 120	52 - 19.5	-
SJ75-3 (60)	22	3450	40 - 120	78.5 - 31.5	-
SJ75-4 (60)	30	3450	40 - 120	107 - 44	-
SJ75-5 (60)	37	3450	40 - 120	134 - 57	-
SJ75-6 (60)	45	3450	40 - 120	160 - 70	-
SJ75-7 (60)	45	3450	40 - 120	188 - 83	-
SJ75-8 (60)	55	3450	40 - 120	214 - 97	-
SJ75-9 (60)	63	3450	40 - 120	240 - 110	-
SJ75-10 (60)	75	3450	40 - 120	267 - 123	-
SJ75-11 (60)	75	3450	40 - 120	292 - 135	-
SJ95-1 (60)	7.5	3450	50 - 130	25 - 8.5	-
SJ95-2 (60)	15	3450	50 - 145	52 - 5	-
SJ95-3 (60)	22	3450	50 - 145	78.5 - 9	-
SJ95-4 (60)	30	3450	50 - 145	105 - 15	-
SJ95-5 (60)	37	3450	50 - 145	133 - 20	-
SJ95-6 (60)	45	3450	50 - 145	160 - 26	-
SJ95-7 (60)	55	3450	50 - 145	187 - 32	-
SJ95-8 (60)	63	3450	50 - 145	214 - 37	-
SJ95-9 (60)	63	3450	50 - 145	242 - 45	-
SJ95-10 (60)	75	3450	50 - 145	269 - 52	-
SJ120-1-1 (60)	15	3450	70 - 170	25 - 16.5	-
SJ120-1 (60)	18.5	3450	70 - 170	32.5 - 25.5	-
SJ120-2-2 (60)	25	3450	70 - 170	48.5 - 36.5	-
SJ120-2-1 (60)	30	3450	70 - 170	58.5 - 43.5	-
SJ120-2 (60)	37	3450	70 - 170	66 - 52	-
SJ120-3-2 (60)	45	3450	70 - 170	80.5 - 62.5	-
SJ120-3-1 (60)	45	3450	70 - 170	91.5 - 70	-
SJ120-3 (60)	55	3450	70 - 170	99.5 - 78.5	-



Model	kW	rpm	Flow (m3/h)	Head (m)	Weight kg
SJ120-4-2 (60)	63	3450	70 - 170	114.5 - 89	-
SJ120-4-1 (60)	63	3450	70 - 170	124.5 - 98	-
SJ120-4 (60)	75	3450	70 - 170	132.5 - 105	-
SJ120-5-2 (60)	75	3450	70 - 170	149.5 - 115	-
SJ120-5-1 (60)	90	3450	70 - 170	158.5 - 126	-
SJ120-5 (60)	90	3450	70 - 170	166 - 131	-
SJ120-6-2 (60)	90	3450	70 - 170	182.5 - 139.5	-
SJ120-6-1 (60)	110	3450	70 - 170	192.5 - 150.5	-
SJ120-6 (60)	110	3450	70 - 170	199.5 - 159.5	-
SJ120-7-2 (60)	110	3450	70 - 170	215 - 164	-
SJ150-1-1 (60)	15	3450	90 - 200	27.5 - 19.5	-
SJ150-1 (60)	22	3450	90 - 200	36 - 28	-
SJ150-2-2 (60)	30	3450	90 - 200	53 - 40	-
SJ150-2-1 (60)	37	3450	90 - 200	63.5 - 49	-
SJ150-2 (60)	45	3450	90 - 200	71.5 - 56.5	-
SJ150-3-2 (60)	55	3450	90 - 200	88 - 67	-
SJ150-3-1 (60)	63	3450	90 - 200	98.5 - 76.5	-
SJ150-3 (60)	63	3450	90 - 200	109.5 - 85.5	-
SJ150-4-2 (60)	75	3450	90 - 200	126 - 95.5	-
SJ150-4-1 (60)	90	3450	90 - 200	136.5 - 105.5	-
SJ150-4 (60)	90	3450	90 - 200	147 - 115.5	-
SJ150-5-2 (60)	110	3450	90 - 200	163 - 124	-
SJ150-5-1 (60)	110	3450	90 - 200	173.5 - 134	-
SJ150-5 (60)	110	3450	90 - 200	184 - 145	-
SJ200-1-B (60)	30	3450	120 - 260	38 - 26.5	-
SJ200-1-A (60)	37	3450	120 - 260	43 - 32	-
SJ200-1 (60)	45	3450	120 - 260	54 - 46	-
SJ200-2-2B (60)	55	3450	120 - 260	74 - 52	-
SJ200-2-2A (60)	75	3450	120 - 260	83.5 - 63	-
SJ200-2-B (60)	75	3450	120 - 260	92 - 72.5	-
SJ200-2-A (60)	90	3450	120 - 260	96.5 - 78	-
SJ200-2 (60)	90	3450	120 - 260	110.5 - 93	-
SJ200-3-2B (60)	110	3450	120 - 260	129 - 100	-
SJ200-3-A-B (60)	110	3450	120 - 260	134 - 104	-
SJ200-3-2A (60)	110	3450	120 - 260	139.5 - 111	-

Performance is for clean water at 20 C unless stated, as published in the CNP catalogue. The ranges show the first and last points of each performance curve. For a datasheet with the full curve and dimensions, open the model page.